



BV LCIE CHINA  
(Ningbo Branch)  
Number

N° 1899AB09AARE00119

**LCIE**

# ATTESTATION of conformity with European Directives

**Product** : PV inverter (Grid-tied photovoltaic inverter)

**Reference** : NAC20K-DT, NAC25K-DT, NAC30K-DT, NAC33K-DT

**Trade mark** : --

**Issued to** : Renac Power Technology Co.,Ltd

**Address** : Building 6, No.2, West Jinzhi Road, High-Tech District, Suzhou City, Jiangsu Province

**Manufacturer** : Renac Power Technology Co.,Ltd

**Technical characteristics** : Refer to the next page

The submitted sample of the above equipment has been tested for **CE** marking according to following European Directive and following standards:

### Electromagnetic Compatibility Directive 2014/30/EU

Standards	Report number	Report date
EN 61000-6-3:2007+A1:2011 EN 61000-6-2:2005 EN 61000-3-2:2014 EN 61000-3-3:2013	ABRE-18AU2503VTNBPB	Dec 06, 2018

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product  
The **CE** marking may be affixed if all relevant and effective European Directives with **CE** are applicable

Ningbo (P.R. China), Dec 06, 2018



This document shall not be reproduced, except in full, without the written approval of BV LCIE China (Ningbo Branch).  
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA (Ningbo Branch)  
必维欧亚电气技术咨询服务(上海)有限公司-宁波分公司  
Version 1.0/2018.06.10

Building B, No.66 Qingyi Road, Hi-Tech Zone, Ningbo, Zhejiang, China

Tel: +86 574 8709 1078  
Fax: +86 574 87907993  
Email: contact@cn.bureauveritas.com



**LCIE**

# ATTESTATION of conformity with European Directives

## Technical Parameter

Model / Type.....	NAC20K-DT	NAC25K-DT	NAC30K-DT	NAC33K-DT
MPP DC voltage range [V].....	250-950			
Max. Input DC voltage [V].	1000			
Max Input DC current [A]..	20/20	20/30	30/30	
Output AC voltage [V].....	230, 3/N/PE, 50/60Hz			
Max. Output AC current [A].....	32(per phase)	40(per phase)	43(per phase)	48(per phase)
Max. Output power [kVA]..	22	27,6	30	33

This document shall not be reproduced, except in full, without the written approval of BV LCIE China (Ningbo Branch).

Information given in this document, are related to the tested specimen of the described electrical sample.