

ATTESTATION

of conformity with European Directives

Product : PV inverter (Grid-tied photovoltaic inverter)

Reference: NAC6K-DT, NAC8K-DT, NAC10K-DT, NAC12K-DT, NAC15K-DT

Trade mark --

Issued to : Renac Power Technology Co.,Ltd

Address : Building 6, No. 2, West Jinzhi Road, High-Tech District, Suzhou City,

Jiangsu Province

Manufacturer : Renac Power Technology Co.,Ltd

Technical characteristics: Refer to the next page

The submitted sample of the above equipment has been tested for C marking according to following European Directive and following standards:

Electromagnetic Compatibility Directive 2014/30/EU

| Standards | Report number | Report date | |
|--|---------------------|--------------|--|
| EN 61000-6-3:2007+A1:2011 EN 61000-6-2:2005 EN 61000-3-2:2014 EN 61000-3-3:2013 | ABRE-18AU2506VTNBPB | Nov 28, 2018 | |

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product The CE marking may be affixed if all relevant and effective European Directives with CE are applicable

Ningbo (P.R. China), Nov 28, 2018





This document shall not be reproduced, except in full, without the written approval of BV LCIE China (Ningbo Branch). Information given in this document, are related to the tested specimen of the described electrical sample.

Tel: +86 574 8709 1078

Fax: +86 574 87907993

Email: contact@cn.bureauveritas.com



ATTESTATION

of conformity with European Directives

Technical Parameter

| Model / Type: | NAC6K- DT | NAC8K- DT | NAC10K- DT | NAC12K- DT | NAC15K- DT | |
|-----------------------------|----------------------|-----------------|---------------|-----------------|---------------|--|
| MPP DC voltage range [V]: | 250-950 | | | | | |
| Max Input DC voltage [V]: | 1000 | | | | | |
| Max Input DC current [A]: | 12,5 | 12,5/12,5 | | | 20/12,5 | |
| Output AC voltage [V]: | 230, 3/N/PE, 50/60Hz | | | | | |
| Max. Output AC current [A]: | 9,6 (per phase) | 12,8(per phase) | 16(per phase) | 19,2(per phase) | 24(per phase) | |
| Output power [VA]: | 6000 | 8000 | 10000 | 12000 | 15000 | |